

Technical Data Sheet

B7782 – Gasket Remover

Revised 03.08.10



BARNWELL
THE SEAL OF APPROVAL

B7782 Gasket Remover

PRODUCT DESCRIPTION

B7782 is a spray applied foaming liquid designed to remove paint and gaskets. It can be used on most common surfaces. B7782 can be used on both horizontal and vertical surfaces, it penetrates deeply into paint and after a few minutes marks are easily removed by rinsing with water.

APPLICATIONS

B7782 Can be used on most common surfaces including brick, stone, metals and concrete.

INSTRUCTIONS FOR USE

Shake can and spray directly and liberally onto affected area. Allow to penetrate (2 minutes to 1 hour depending on type of stain) then wipe away and rinse area with water. For multiple layers, dry area and repeat process. B7782 should not be allowed to dry out before cleaning the treated area.

STORAGE

Storage temperature should be kept below 50°C. Storage area should be out of direct sunlight.

Regulation

A new ban on some supply and use of paint strippers containing the hazardous substance dichloromethane (DCM). For the purpose of this ban, the term "paint stripper" is taken to mean DCM (or mixtures containing it) intended for stripping paint, varnish or lacquer. The new ban makes a distinction between three types of use.

"**Industrial**" use of paint stripper in "industrial installations" (i.e. facilities where paint stripping takes place) this is allowed to continue as long as certain safe working practices are followed. "**Professional**" use by workers where this takes place away from an industrial installation. This will be banned, but UK can choose to allow continued safe use by specifically trained professionals. "**Consumer**" use by the general public such as DIY. Supply to consumers is banned. **This product contains dichloromethane**

TECHNICAL FEATURES

Temperature range	-40°C - 121°C
-------------------	---------------

HEALTH & SAFETY IN USE

Pressurised container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not spray on to an open flame or any incandescent material. Keep away from sources of ignition. This technical information sheet for does not constitute a Material Safety Data Sheet (MSDS). Before using this product ensure you have read and fully understand the MSDS.

PRESENTATION

Aerosol.....400ml

PRECAUTIONS: This product and the auxiliary materials normally combined with it are capable of producing adverse health effects ranging from minor skin irritation to serious systemic effects. None of these materials should be used, stored, or transported until the handling precautions and recommendations as stated in the Material Safety Data Sheets (MSDS) for this and all other products being used are understood by all persons who will work with the product. Warranty: All products purchased from or supplied by Bondloc are subject to terms and conditions set out in the contract. Bondloc warrants only that its product will meet those specifications designated as such herein or in other publications. All other information supplied by Bondloc is considered accurate but are furnished upon the express condition the customer shall make its own assessment to determine the product's suitability for a particular purpose. Bondloc makes no other warranty, either express or implied, including those regarding such other information, the data upon which the same is based, or the results to be obtained from the use thereof; that any product shall be merchantable or fit for any particular purpose; or that the use of such other information or product will not infringe any patent.